



Made under

ISO 14001

ISO 9001

>> Type of uses

This equipment has been designed to protect the user against the risk of injury to the eyes and face by mechanical impacts. Forestry, maintenance of parks and gardens, pruning...

>> Technical features

- ✓ The protective face shield is composed of an adjustable polypropylene headgear, a yellow browguard and a clear swivel-up mesh visor 305 x 195 mm.
- ✓ The headgear is composed of 2 lateral hinges which allow the visor rotation on the headgear with possibility to adjust the fastening couple screw/nut.
- ✓ A comfortable sweatband is fixed on the front of headband.
- ✓ The two upper straps allow the height adjustment by pin-lock.
- ✓ The adjustment around the head is obtained by a ratchet lock system.
- ✓ The visor is fixed on the headgear by three swivel locks.
- ✓ **Weight:** 204 g.
- ✓ Possibility to buy only the spare visor (sold separately). Ref - **ACC825** (305 x 195 mm)
- ✓ **Packing:**
 - **EVA825:** Carton of 60 pieces.
 - **ACC825:** Carton of 200 pieces.
- ✓ **Subpackaging:**
 - **EVA825:** Box of 10 pieces.
 - **ACC825:** Each piece under individual polybag.



Learn more www.singer.fr

>> Advantages

- ✓ Very light weight product and easy to use.
- ✓ Front comfortable sweatband
- ✓ Possibility to replace the used or impaired visor (see our reference ACC825).
- ✓ Easy adjustment of headgear with ratchet.

>> Conformity

This product has been tested according to the following European Standard:

- ✓ **EN 1731: 1997.** Personal eye protection. Mesh eye and face protectors.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (**module B**) issued by **CERTOTTICA**. Notified body n°**0530**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection EN 1731	Symbol F	Impact resistant against high speed particles (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
		The screen is without special filtering action

Your distributor **SINGER® SAFETY**

SINGER®
safety